

SUMP & SEWAGE ACCESSORIES

ACCESS.

Water Systems

Sump and Sewage

Lawn and Sprinkler

Electric Motor Driven

Engine Driven

Frame Mount

Hand Pumps

Irrigation and Industrial



SDH

SUMP DRAINER HOSE - WITH ADAPTOR AND CLAMP			
Model No.	Order No.	Ship Wt. (lbs.)	Description
SDH	626150	2.5	24 ft. x 1 1/4" with 1 1/4" male adaptor and clamp.



627830

UNIVERSAL SUMP PUMP CHECK VALVE		
Order No.	Ship Wt. (lbs.)	Description
627830	0.5	1 1/4" NPT - Fits all Monarch sump pumps.



627831

SEWAGE ADAPTOR KIT		
Order No.	Ship Wt. (lbs.)	Description
620385	6	Converts 2" NPT discharge to 3" for WS Series pumps.

SEWAGE CHECK VALVE		
Order No.	Ship Wt. (lbs.)	Description
627831	1	2" NPT-ABS plastic - used on WS52S-FP & WSV52S-FP package. Includes pipe coupling - both ends.


MECHANICAL ALTERNATORS - OPEN TANK OPERATION - MECHANICAL TYPE							
Model No.	Order No.	Ship Wt. (lbs.)	Maximum HP Rating				Description
			1 Phase		3 Phase		
			115V HP	230V HP	230V HP	460/575V HP	
9038AG1	224500	2	1 1/2	2	3	1	Provides a simple positive means of alternating the operation of two pumps on a duplex system with a common tank.



9036-GG2

LIQUID LEVEL CONTROLS - OPEN TANK OPERATION - MECHANICAL TYPE								
Model No.	Order No.	Ship Wt. (lbs.)	Maximum HP Rating				Poles	Replacement Points
			1 Phase		3 Phase			
			115V HP	230V HP	230V HP	460/575V HP		
9036-DG2	224410	2	1 1/2	2	3	1	2	224360
9036-GG2	224420	2	2	3	5	5	2	224350

COPPER FLOATS AND BRASS RODS - FOR LIQUID LEVEL CONTROLS		
Order No.	Diameter	Description
FLOATS		
224610	6"	Spud type, 1/4" 20 UNC.
224630	7"	Centre hole type, 1/2" I.D.
RODS		
622250	1/4" O.D.	6 ft. long brass rod threaded 1/4" 20 UNC less float stops.
224720	3/8" O.D.	6 ft. long brass tube, less float stops.
263920		12 ft. long brass tube, less float stops.
435960		Float stops for brass tubing, (usable on 1/4" or 3/8" tubing).




LIQUID LEVEL CONTROLS - ELECTRODE TYPE (MAY ALSO BE USED WITH PROBE HOLDER AND RODS)					
Model No.	Order No.	Ship Wt. (lbs.)	Max. HP	Voltage	Description
	622190	4	1	115	For sump or sewage pump applications, with high level cut-in and low level cut-out operation.
	622170	4	1	230	

SUMP & SEWAGE ACCESSORIES

FLOAT SWITCHES - MECHANICAL - SJE MICROMASTER						
Model No.	Order No.	Ship Wt. (lbs.)	Voltage	Max Amps	Cord Length	Where Used
10MMD1WP	639643	1	120	10	10'	ESP33
20MMD1WP	639630	2	120	10	20'	ESP50
FLOAT SWITCHES - MECHANICAL - SJE MICROMASTER PLUS						
10MMPD1WP	639685	1	120	13	10'	
20MMPD1WP	639686	2	120	13	20'	WS30, WS51, WS52, WSV50, WSV52
FLOAT SWITCHES - MECHANICAL - SJE PUMPMASTER						
Model No.	Order No.	Ship Wt. (lbs.)	Voltage	Max Amps	Cord Length	Description
20PMD2WP	639603	2	230	13	20'	WS50HAM-12-20, WS50AM-12-20
30PMD2WP	639604	3	230	13	30'	WS50AM-12, WS50HAM-12, WS52HAM-12
FLOAT SWITCHES - MECHANICAL - SJE PUMPMASTER PLUS						
20PMPD1WP	639606	2	120	15	20'	WS50AM-20, WS50HAM-20
30PMPD1WP	639607	3	120	15	30'	WS50AM, WS50HAM, WS52HAM
20PMPD2WP	639609	2	230	15	20'	WS100HAM-12-20, WS200GAM
30PMPD2WP	639610	3	230	15	30'	WS100HAM-12, WS102HAM-12
FLOAT SWITCHES - MERCURY ACTIVATED - SJE JR SUPER SINGLE						
Model No.	Order No.	Ship Wt. (lbs.)	Voltage	Max Amps	Cord Length	Description
20JSSD1WP	639990	2	120	13	20'	Pump down operation.
20JSSU1WP	639993	2	120	13	20'	Pump up operation.
FLOAT SWITCHES - MERCURY ACTIVATED - PARAMATIC IND (PIL)						
Model No.	Order No.	Ship Wt. (lbs.)	Voltage	Max Amps	Cord Length	Description
PIL10D	633738	4	115/230	15	33	Pump Down Operation
PIL10U	633737	4	115/230	15	33	Pump Up Operation
FLOAT SWITCHES - MERCURY ACTIVATED - PARAMATIC IND (PIL)						
Model No.	Order No.	Ship Wt. (lbs.)	Voltage	Max Amps	Cord Length	Description
10VM1WP120	639615	1	120	13	10	Vertical Master Float Switch includes pipe mount bracket.
20VM1WP120	639994	2	120	13	20	



639630



639615



622199